



TECHNICAL DATA SHEET

Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

SYNT F948 5W20

ED-01
ENERO-2019

DESCRIPTION:

100% Synthetic high performance engine lubricant, specially designed for FORD and for manufacturers requiring low friction and low viscosity HTHS oils (≥ 2.6). Specially developed for latest generation vehicles, equipped with gasoline or diesel engines, naturally aspirated or supercharged, direct or indirect injection, Euro 6, such as FORD, JAGUAR, LAND ROVER, CHRYSLER, JEEP.

FEATURES:

- Bonds to metal surfaces making engine parts more resistant to wear and decreases friction.
- Combines synthetic technology to provide greater protection in both high and low temperature applications.
- Offers continued protection in all driving styles and temperatures
- Provides superior performance in extreme cold start conditions.
- Long Life

HOW TO USE IT:

Before use, always check the vehicle's maintenance manual. Direct uses SPECIAL : FORD, JAGUAR, LAND ROVER, CHRYSLER, JEEP

TECHNICAL DATA:

Description :	Oil 100 % synthetic
Aspect :	Clear and bright fluid
Viscosity at 100°C :	ASTM D-445 5.6-9.3 cST.
Viscosidad index:	ASTM D2270 150 minimum

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS:

ACEA C5

API SN

FORD WSS M2C 948 B (Compatible 913 A, 913 B, 913 C, 925 A & 925 B)

JAGUAR LAND ROVER

STJLR.03.5004