



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobí del Penedès (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

MULTIGRADE 15W40 TDI-GTI

ED-06
ENERO 2019

DESCRIPTION

High performance multigrade mineral oil formulated for petrol and diesel engines (GTI-TDI).

FEATURES

Good thermal stability, important to withstand the high operating temperatures of this type of engine.
High resistance to oxidation and oil ageing.
Easy cold start and good lubrication at all engine temperatures. Very shear stable oil. Suitable for normal (road) and severe service (city) driving.
NOT SUITABLE FOR DPF

TECHNICAL DATA

Aspect :	Clear and bright fluid
Viscosity at -30°C :	ASTM D-5293 7000 cP maximum
Viscosity at 100°C :	ASTM D-445 12.5 - 716.3 cST.
Viscosity index	ASTM D2270 140 minimum

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

APPLICATIONS

It is used especially for naturally aspirated or turbocharged petrol and light diesel vehicles with direct or indirect injection. For passenger cars and light commercial vehicles. Not suitable for DPF

QUALITY LEVELS

API SL/CF/CG-4

ACEA A3/B4 (04)

ACEA E3 (96)

MB 228.3 – 229.1

VW 501.01/505.00

MAN M 3275

VOLVO VDS

RENAULT RVI RLD

MTU LEVEL 2