



TECHNICAL DATA SHEET

Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobí del Penedès (Barcelona)
+34938978437 www.iada.es

15W40 THPD E7/E9

ED-01
MARZO-2017

DESCRIPTION

High-end synthetic lubricant for heavy-duty diesel vehicles, with excellent performance. Quality level lubricant ACEA E6-12 is designed to lubricate the new Euro V/VI engines with low sulphated ash (Low SAPS) emissions reduction, diesel particulate filter (DPF), exhaust gas recirculation (EGR) and diesel particulate filter (DPF) systems, exhaust gas recirculation (EGR) or selective catalyst reduction (SCR) after-treatment systems.

FEATURES

- Aceite lubricante de tecnología sintética de máxima calidad THPD (Top High Performance Diesel).
- Apto para todos los motores Euro IV y V.
- Altas cualidades antidesgaste y anticorrosivas, bajo contenido en cenizas (LOW SAPS).
- Es compatible con todo tipo de carburantes (diesel, GLP, GNC y biodiesel).
- Reduce la formación de lacas, barnices y residuos en el motor, mejorando su lubricación y aumentando su durabilidad.

HOW TO USE IT

Ideal oil for mixed fleets. Especially recommended for the lubrication of Euro V and VI Heavy Duty Diesel engines, equipped with both DPF (Particulate Filter) and SCR (Selective Catalyst Reduction) and VI, equipped with both DPF (Particulate Filter) and SCR (Selective Catalytic Reduction), as well as previous engines, Euro I, II and III, IV, Euro I, II and III, IV. With long oil change intervals in turbocharged engines with or without intercooler and naturally aspirated engines equipped with naturally aspirated engines equipped with aftertreatment systems.

TECHNICAL DATA

Description :	Engine oil 100% synthetic
Aspect :	Bright and clear fluid
Viscosity at 100°C :	ASTM D-445 12.5 - 16.3 cST.
Viscosity index :	ASTM D2270 150 minimum

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS:

API SN/CJ
ACEA E7 / E9
FORD WSS- W2C171-E
Volvo VDS-4
MACK EO-O PREMIUM PLUS
DDC 93K-218
Cummins CES 20081
Caterpillar ECF-3