



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

7 SPEED ATF 236.14

DESCRIPTION:

ED-02
JUL-14

Lubricante 100 % sintético de altas prestaciones para transmisiones automáticas de turismos, furgonetas monovolúmenes,...

Ofrece una buena protección y lubricación al cambio automático.

Fluido 100 % sintético, especialmente diseñado para Mercedes con caja de cambios automática RWD de 7 velocidades (NAG-2) y todos los modelos donde se requieran MB-Approval 236.14.

FEATURES:

Provides optimum protection against wear and ageing, protects gears thanks to its anti-wear properties. The additives present in the formulation protect against corrosion, oxidation and extend the life of the product. It is able to reduce fuel consumption by reducing gearbox friction, due to which gears become smoother and faster. Its viscosity properties are optimal even at low temperatures. High viscosity index.

HOW TO USE IT:

We recommend our ATF 236.14 for Mercedes rear-wheel drive (RWD) and 4x4 (AWD-All Wheel Drive) cars, SUVs and light vehicles, equipped with automatic gearboxes.

Suitable for Mercedes models equipped with 7-speed RWD gearboxes (NAG-2) and all models requiring MB-approval 236.14.

Suitable for Mercedes 5-speed RWD gearboxes.

Can only be mixed with oils of the same type.

Before use refer to the service manual.

TECHNICAL DATA:

Description :	Lubricant for automatic transmissions	
Color:	Visual	Amber
Viscosity at - 40°C :	ASTM D-445	29.6 cSt
Viscosity at 100°C :	ASTM D-445	6.6 cSt
Viscosity index :	ASTM D-2270	185 minimum

We reserve the right to modify the general characteristics of our products in order to facilitate that our clients benefit from the latest technical advances. For more information about the product, it is recommended to consult the Safety Data Sheet (SDS), available through the Customer Service Center in IADA.

QUALITY LEVELS:

MB 236.14

SFU (suitable for use) : MB 236.1/6/7/9/10/12.