



TECHNICAL DATA SHEET

Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

ATF 6HP

ED-01
FEB-16

DESCRIPTION:

ATF is an automatic transmission oil, formulated from base oils, PAO and special additives. Its low viscosity provides fuel economy, Fuel Economy, thus meeting the most specific OEMS specifications. Not compatible with any ATF fluid. Amber colour.

FEATURES:

- High lubricity even at low temperatures in winter Low freezing point.
- Excellent oxidation stability, good corrosion protection and foaming.
- High thermal and corrosion protection
- Stable against sealing materials..

HOW TO USE IT:

Before using the product, it is important to check the vehicle's service manual: draining is carried out according to the manufacturer's requirements.

TECHNICAL DATA:

Description :	Lubricant for automatic transmissions	
Color:	Visual	Amber
Viscosity at - 40°C :	ASTM D-445	22 - 32 cSt
Viscosity at 100°C :	ASTM D-445	6 - 6.3 cSt
Viscosity index :	ASTM D-2270	150 minimum

We reserve the right to modify the general characteristics of our products in order to facilitate that our clients benefit from the latest technical advances. For more information about the product, it is recommended to consult the Safety Data Sheet (SDS), available through the Customer Service Center in IADA.

QUALITY LEVELS:

ATF M1375.4 - BMW 83220144137 83220142516, 83222305396 (ATF2), FORD Mercon SP XT-6-QSP (6R60, 6R75, 6R80), Jaguar C2C 8432, Land Rover TYK 500050, VW/AUDI G 055005 A1/A2/A6, ZF S671 090 252/3/5.