



TECHNICAL DATA SHEET

Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

DIESEL ANTIFREEZE

ED-04
AG13

DESCRIPTION

Additive to improve the fluidity of cold diesel oil. Extends the range of use of diesel oil by reducing its freezing temperature.

FEATURES

Delays the appearance of crystals in the diesel, which clog the filter and prevent the engine from starting.

APPLICATIONS

In all types of motor vehicles equipped with diesel engines. Also in coaches, lorries, agricultural and public works machinery, etc.

HOW TO USE IT

Add the contents of the 300 cc canister to the fuel tank, which should contain between 30 and 50 litres of fuel. Protection between -17 and -20°C.

If the application is doubled, two 300 cc cans for 30-50 litres of fuel, the protection temperature will be 25-27°C. The freezing point is not doubled as at these temperatures the mixture of additive and fuel behaves differently.

TECHNICAL DATA

Description : Special additive to lower the freezing temperature of diesel fuel.

Aspect : **Visual** Transparent and bright fluid

Color : **Visual** Colorless

pH : 6.0 / 7.0

Density at 20°C : 0.819 / 0.829 gr/cc.

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.