



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobí del Penedès (Barcelona)
+34938978437 www.iada.es

FICHA DATOS TÉCNICOS

DIESEL ANTIFREEZE

ED-03
AG 13

DESCRIPTION :

Additive to improve the fluidity of cold diesel fuel.

FEATURES:

Delays the appearance of crystals in the diesel fuel, which clog the filter and prevent vehicle operating problems, e.g. engine start-up. Improves the fluidity of the fuel. Improves the properties of conventional fuel.

APPLICATIONS:

In all types of diesel-engined motor vehicles. Also in coaches, lorries, agricultural and public works machinery.

HOW TO USE IT:

Add the contents of the container into the fuel tank when it is full.

The contents of the bottle, 1 litre, is enough to add 150 litres of diesel fuel.

Protection against freezing of diesel fuel. Starting temperature of crystallisation: $-17 \pm 1^{\circ}\text{C}$

If the application is doubled, two 1 L cc canisters for 150 litres of fuel, the protection temperature will be $25-27^{\circ}\text{C}$. The freezing point is not doubled as at these temperatures the additive/fuel mixture behaves differently.

TECHNICAL DATA SHEET:

Aspect :	Bright and transparent fluid
-----------------	------------------------------

Density at 20°C :	UNE 26-390	6.0 - 7.0
--------------------------	-------------------	-----------

pH :	UNE 26-389	0.819 – 0.829 gr/
-------------	-------------------	-------------------

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.