

GLYCOGEL ECO G-13 AR-50%

DESCRIPTION

ED-02
SEP 15

Direct use diluted ethylene glycol/glycerine based engine coolant specially formulated for use in Volkswagen light vehicle engines. Uses environmentally friendly technology based on organic acids (OAT) and is contains no nitrites, amines and phosphates (NAP) and no borates. Contains silicate additives that provide protection against fast curing aluminium.

FEATURES

Protection of cooling circuits against cold.
Free of phosphates, nitrites, nitrates and amines. Free of silicates.
Good heat exchange for efficient engine cooling.
Compatible with gaskets, hoses and plastic components. Eliminates the formation of deposits due to its phosphate-free formulation.
phosphate-free formulation.

HOW TO USE IT

No handling required. Direct use. Do not dilute. **This product is not compatible and should not be mixed with other organic coolants.** Not suitable for older cooling systems with copper/brass radiators and heater cores, and especially not for the lead solder they incorporate.

TECHNICAL DATA

Aspect :	Visual	Transparent and bright fluid
Color:	Visual	Violet
Density at (20°C) :	UNE 26-389	1.065 / 1.085 g/ml
PH	UNE 26-390	7.5 / 9.0
Alkaline reserve:	UNE 26-388	4 - 6 ml HCl 0.1M
Freezing point:	UNE 26-391	-35 °C ± 2 °C

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS

- AUDI-SEAT-SKODA-VW: VW TL-774-J – G13