

DESCRIPTION

Direct use coolant - antifreeze, designed for heavy duty vehicles requiring **hybrid technology**, free of nitrite, amine and phosphate with added silicates.

Specially designed for MAN vehicles that require refrigerants of the type; MAN 324-NF.

Due to its technology, it is recommended NOT TO MIX WITH OTHER COOLANTS. **Protection -37°C.**

DIRECT USE. DO NOT DILUTE.

CHARACTERISTICS

It offers an excellent protection on all metals in the cooling system of internal combustion engines.

Protection of refrigerant circuits against cold.

Corrosion properties: protection of the entire system.

Good thermal exchange that allows to effectively cool the motor.

Compatible with gaskets, sleeves, and plastic components.

HOW TO USE IT

Does not require any kind of manipulation. **Direct use. Do not dilute.**

This product **it is not compatible and must not be mixed with any other organic coolants.**

TECHNICAL DATA

Aspect :	Visual	Brilliant and transparent fluid
Color:	Visual	Green-Blueish
Density (20°C) :	UNE 26-389	1.058 / 1.072 g/ml
PH	UNE 26-390	7.5 / 9.0
Alkaline reserve	UNE 26-388	5.0 - 8.0 ml HCl 0.1M
Freezing point	UNE 26-391	-35 °C ± 2 °C

** We reserve the right to modify the general characteristics of our products in order to facilitate that our clients benefit from the latest technical advances. For more information about the product, it is recommended to consult the Safety Data Sheet (SDS), available through the Customer Service Center in IADA.

QUALITY LEVELS

- AS 2108-2004, ASTM D 3306, ASTM D 4985,
- AFNOR NR R 15-061
- SAE J1034
- ÖNORM V 5123
- CUNA NC 956-16
- JIS K 2234:2006,
- SANS 1251:2005,
- SH 0521-1999 and BS 6580:2010
- MB 325.0
- **MAN 324 –NF**
- SAAB 6901599
- JENBACHER TA- Nr. 1000-0201
- DEUTZ H-LV 0161 0188
- OPEL/GENERAL MOTORS B040 0240
- MTU – MTL 5048
- GERMAN ARMY TL 6850-0038/1
- LIEBHERR MACHINES BULLE – TLV 035, TLV 23009 A
- BEZ. REG ARNSBERG, DEP OF MINING A ENERGY 84.12.22.63-2001-2