

DESCRIPTION:

Highly refined hydraulic fluid with antioxidant and antifoam additives. For presses, hydraulic jacks, agricultural machinery, etc. ISO VG 46.

CHARACTERISTICS:

- Long life hydraulic oil.
- Good stability against oxidation, which prolongs the useful life of the oil.
- Good filterability.
- Improves lubrication capacity thanks to minimal foaming.
- It has no corrosive effects on copper alloys.

APPLICATIONS:

Its field of application includes hydraulic presses and jacks, machine tools, agricultural machinery and of public works, forklifts, reducers, compressors and in general all kinds of power transmission, in which a Hydraulic Oil is recommended according to the ISO HL specification.

TECHNICAL DATA:

Description :	Hydraulic Oil 100% mineral.	
Aspect :	Visual	Fluido brillante y transparente, color rojo o ambar.
Viscosity at 40°C :	ASTM D-445	41.4 – 50.6 cSt
Viscosity at 100°C :	ASTM D-445	6.9 cSt
Vicosity Index:	ASTM D2270	100
Freezing point:	ASTM D-97	- 28 °C
Inflammation Point:	UNE 51-023	210 °C

QUALITY LEVELS:

DIN 51524/1 HL
Denison HF-2
Vickers I-286-S