



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobí del Penedès (Barcelona)
+34938978437 www.iada.es

FICHA DATOS TÉCNICOS

IATRACK J20D - LV

ED-03
MAY 13

DESCRIPTION :

Highly refined lubricating oil. Its specific application is in tractors, in the hydraulic system, transmission and disc brakes immersed in an oil bath. Viscosity grade SAE 10W30. UTTO (Universal Tractor Transmission) type oil.

FEATURES:

Excellent high temperature performance contributes to less deposit build-up and longer service life. Controls moisture build-up, oxidation and deposit formation due to heat. Extends clutch life. Recommended for equipment with common reservoirs or independent hydraulic and transmission systems, including systems with wet clutches and brakes. Superior performance with quoted specifications.

APPLICATIONS:

- The right oil for your agricultural and gardening equipment. This premium lubricant offers consistent performance in a wide range of operating conditions for:
-
- Transmissions and differentials with wet brakes in an oil bath.
- Gearboxes with hydraulic brakes.
- Gearboxes with hydraulic by-product systems.
- Hydraulic transmissions.

TECHNICAL DATA:

Description :	Mineral oil type UTTO (Universal Tractor Transmisión Oil).	
Aspect :	Visual	Bright and clear fluid
Viscosity at 40°C :	ASTM D-445	30-45
Viscosity at 100°C :	ASTM D-445	7-8 cSt
Viscosity index :	ASTM D2270	160 minimum

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS:

John Deere J20D