



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobí del Penedes (Barcelona)
+34938978437 www.iada.es

FICHA DATOS TÉCNICOS

IATRACK 20

DESCRIPTION :

ED-04
MAY 13

Highly refined lubricating oil. Its specific application is in tractors, in the hydraulic system, transmission and disc brakes immersed in an oil bath. Viscosity grade SAE 10W30. UTTO (Universal Tractor Transmission) type oil.

FEATURES:

High-performance UTTO-type lubricating oil for transmissions, differentials, axles, etc. that meets the lubrication requirements of most tractor manufacturers. Excellent power transmission and high thermal stability. Eliminates vibrations and favours optimum brake operation, avoiding noise. Thanks to its formula, it reduces overheating due to internal friction, maintaining correct functioning of brakes and clutches in demanding working conditions. Good resistance to accidental water contamination. Good protection against extreme pressure, extending gear life. Contains corrosion and rust inhibitors. High fluidity at low temperatures, providing easy cold engine starting and better pumpability. High lubricant film stability, essential under extremely severe operating conditions. Compatible with all gasket and seal materials commonly used in this type of machinery.

APPLICATIONS:

Specially developed for the lubrication of all transmission components, hydraulics and oil immersed disc brakes in tractors and agricultural machinery. Universal Tractor Transmission Oil (UTTO). The product should not be used for engine lubrication. For this application there are other specific products such as IADA STOU Multifunctiona

TECHNICAL DATA:

Description :	UTTO (Universal Tractor Transmission Oil) type mineral oil.. Visual
Aspect :	Bright and clear fluid
Viscosity at 100°C :	ASTM D-445 9 - 10 cSt
Viscosity index :	ASTM D2270 150 minimum

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS:

Allison C-4
API GL-4
Carterpillar TO-2
CNH MAT 3525, 3526
Ford M2C134D, M2C86B/C
JCMAS HK P-041
J.I. Case / Case international MS-1204, 1206, 1207, 1209
John Deere J20C

Kubota UDT fluid
Massey Ferguson M1135/1143/1145
NH410B, NH420A
Oliver Type 55/5J/Q1802
Sauer Sunstrand/Danfoss: Hydrostatic trans Fluid
Vickers/Eaton: M2950S / I-280-S
Volvo VB101
White Q1705/1722/1766/1766B/1802/1826