

DESCRIPTION:

100% synthetic low-viscosity lubricant especially for manual and semi-automatic gearboxes, allowing optimised cold starting and excellent behaviour at stable viscosity/temperature. SAE 75W gear oil, special dry clutch.

FEATURES:

- Viscosity grade suitable for the modern demands of the mechanisms that require it. Good lubricating and lubricating properties. Good extreme pressure properties. High anti-wear characteristics. High thermal stability. High resistance to corrosion and rust formation. All-weather use.
- Good emulsifying qualities. Low foaming.

TECHNICAL DATA:

Aspect :	Transparent and bright fluid			
Viscosity at 40°C :	ASTM D445	28-46	cSt	
Viscosity at 100°C :	ASTM D445	5.8	- 7.2	cSt.
Viscosity index:	UNE 26390	>160		

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

APPLICATIONS:

This product is specially formulated for gearboxes for which low viscosity manual transmission fluids are recommended. Suitable for high mechanical and thermal stresses of transmission oils, even at longer oil change intervals, it is a fully synthetic gear oil for manual and semi-automatic transmissions in dry clutch (DCT).

QUALITY LEVELS:

API GL-4

GM MTF 0063

BMW MTF LT-2 / BMW MTF LT-3 2300 7533 818, BMW MTF LT-3 83 22 0 396 706, BMW MTF LT-3 83 22 7 533 818

PSA Standard 9730A8

TOYOTA 08885-810010 08885-81081

FORD WSS-M2C200-D2

FIAT 9.55550-MZ6

Mercedes A001989840309 MB 235.10

NISSAN LV MTF-1

Suzuki 99000-22B27-036

VW TL 521 71 – TL 521 78 – TL 726 – TL 525 12

VW/AUDI G060 726 A2 - G052 171 A2 - G052 178- G 052 726 A2 – G052 798 - G052 512 A2 G009317A2

VOLVO 1161839 – 1161838