



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

MULTIAXLE 75W80 GL5

DESCRIPTION:

ED-06
OCT-2020

Lubricante para engranajes sintético par turismos, camiones y autobuses. Formulado con aditivos de Extrema presión para diferenciales y arboles de transmisión con especificación GL-5.

FEATURES:

- - Its E.P. properties provide adequate wear protection for metal surfaces.
- - It has a high resistance to degradation of the oil itself at high temperatures.
- - The presence of synthetic bases in its formulation gives it a high oxidation stability.
- - Extended oil change, greater durability.
- - Easy cold start.

APPLICATIONS:

For all types of industrial gears and gearboxes with closed crankcase. In general, where a lubricating oil of the extreme high pressure type is required, but with relatively low viscosity.

TECHNICAL DATA:

Aspect :	Transparent and bright fluid
----------	------------------------------

Viscosity at 100°C :	ASTMD-445	7-11 sCT
----------------------	-----------	----------

Viscosity index:	ASTM D2270	120 minimum
------------------	------------	-------------

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS:

API GL – 5

MAN 342 M-2

ZF 12E

ZF 21A