



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobí del Penedès (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

MULTIAXLE 85W140 GL5

ED-04
OCT-2020

DESCRIPTION:

Mineral gear lubricant for cars, trucks and buses. Formulated with extreme pressure additives for differentials and driveshafts to GL-5 specification.

FEATURES:

- - Its E.P. properties provide adequate wear protection for metal surfaces.
- - It has a high resistance to degradation of the oil itself at high temperatures.
- - The presence of synthetic bases in its formulation gives it a high oxidation stability.
- - Extended oil change, greater durability.
- - Easy cold start.

HOW TO USE IT:

The requirements of the car and gearbox manufacturers must be observed.

Heavy-duty axles and final drives requiring API GL-5 performance level Light-duty and heavy-duty trucks and commercial vehicles Industrial machinery: construction, mining, quarrying, mining and agriculture.

Not suitable for Limited Slip (LS) rear axles.

TECHNICAL DATA:

Aspect :	Transparent and bright fluid
----------	------------------------------

Viscosity at 100°C :	ASTM D445	24-32	cSt.
----------------------	-----------	-------	------

Viscosity index:	ASTM D2270	95 minimum
------------------	------------	------------

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS:

API GL – 5

MAN 342 M-1

MIL-L-2105D

MB 235.0

MACK GO-J

VOLVO 97309/10