



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

FICHA DATOS TÉCNICOS

HD OIL TREATMENT

ED-01
OCTUBRE-19

DESCRIPTION :

Engine oil additive for petrol or diesel vehicles. With molybdenum disulphide.

FEATURES:

Ensures optimum lubrication, e.g. during cold starts.
Increases engine compression and therefore engine power. Reduces fuel and oil consumption.
Reduces wear.
Increases oil pressure.
Reduces engine noise.

APPLICATIONS:

Especially intended for car engines, which already have a certain amount of wear due to a long service time, both petrol and diesel engines.
For oils in service to restore the initial viscosity characteristics by extending the change. No not recommended to be added at oil change.
Compatible with exhaust treatment elements, particulate filters or catalytic converters.

HOW TO USE IT:

The contents of the container shall be added to the engine oil, one container is sufficient for the treatment of 15 to 20 litres of oil.
The operation must be carried out with the engine stopped, but at operating temperature.

TECHNICAL DATA:

ASPECT:	Fluid with high viscosity.
----------------	----------------------------

Viscosity at 100°C :	ASTM D-445	80-87 cSt
-----------------------------	-------------------	-----------

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.