



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

TECHNO + SAE 5W40 FULLY SYNTHETIC

ED-03
APRIL-14

DESCRIPTION :

100% synthetic lubricant oil specially formulated for high performance diesel and gasoline engines. Special formulation for TDI engines (pump injector): VW-SEAT-AUDI-SKODA, which use the unit injection pump equipment according to specification 505.01. It meets BMW requirements for its gasoline and diesel vehicles equipped with or without particulate filters, with expanded oil change services (BMW specification LL-04). For Euro IV and earlier engines. Medium content in SAPS.

CHARACTERISTICS:

Good flowability at low temperature, which facilitates cold start by reducing internal engine wear.
High viscosity index, which allows to keep the viscosity adequate to the different working temperatures of the engine.
Due to its formulation with 100% synthetic bases, it is a lubricant of low volatility and therefore of reduced consumption. Oil with good resistance and stability to shear.
High thermal stability and high resistance to oxidation. Excellent protection against wear and corrosion.
Lubricant with high detergent and dispersing power. It avoids and controls the formation of deposits and has clear benefits in the cleaning of the pistons.
Extended oil changes, longer durability.
Oil with high levels of quality that meets the latest requirements of the automotive industry.
Oil with medium content in SAPS to fulfill the environmental requirement EURO IV (reduction of pollutant emissions).

HOW TO USE IT:

For the most modern gasoline and diesel engines conventional or direct injection, whether natural aspiration, supercharged and / or multivalves, and in particular for VW-AUDI-SEAT-SKODA vehicles that require the use of lubricants with VW quality level 505.01, for BMW vehicles according to quality level LL-04 and for Mercedes Benz according to quality level MB 229.51.
Complies with the latest standards for compliance with the environmental requirement EURO IV.

TECHNICAL DATA:

Aspect :	Visual	Bright and clear fluid
Viscosit at 100°C :	ASTM D-445	9.3 – 12.5 cSt
Viscosity index :	ASTM D2270	160 minimum

QUALITY LEVELS:

API SN
ACEA C3
MB 229.51
VW 502.00/505.01 (pump injector)
BMW LL- 04
General Motors Dexos 2
Porsche A40