



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

SUPER EVOLUTION 20W50

ED-01
MARCH-24

DESCRIPTION :

Multigrade mineral oil for diesel and gasoline engines with improved oxidant characteristics.

CHARACTERISTICS:

Suitable for Central and Southern European climatic conditions and recommended for all seasons. Suitable for engines with certain wear and consumption problems. Excellent wear and corrosion protection. Extends the life of engine components. Suitable for normal (road) and severe (city) driving.

HOW TO USE IT:

In any type of 4 stroke gasoline engine and light duty diesel engine, whether they are atmospheric or turbo charged.

TECHNICAL DATA:

Aspect :	Bright and transparent fluid		
Viscosity at 40°C	145	cSt.	
Viscosity at 100°C :	16.3 – 21.9	cSt.	
Viscosity index: ASTM D5293	>=130		
Viscosity at -30:	UNE 26-388	< 9500	cP.

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS:

API SL/CF/CG-4
ACEA A3/B4
ACEA E2/ E3
MB 228.1-228.3 – 229.1
VW 501.01/505.00
MAN 271
MAN M 3275
VOLVO VDS
MTU LEVEL 2