

DESCRIPTION

Direct use antifreeze coolant, designed for heavy duty vehicles requiring Si-OAT Technology, nitrite, amine and phosphate free product with added silicates.

Specially designed for MAN vehicles for use in vehicles requiring MAN 324 Type Si-OAT coolants, including vehicles built from December 2012. Approved for use in trucks with Euro VI engines. Colour Violet-Pink.

FEATURES

Protection of cooling circuits against cold.

Excellent protection against metals. Anti-corrosion properties: protection of the entire system. Good heat exchange for efficient engine cooling.

Compatible with gaskets, hoses and plastic components.

HOW TO USE IT

Does not require any kind of manipulation. Direct use, do not dilute.

TECHNICAL DATA

Aspect :	Visual	Transparent and bright fluid
Color:	Visual	Pink-Violet
Density (20°C) :	UNE 26-389	1.070 / 1.080 g/ml
PH	UNE 26-390	7.5 / 9.0
Alkaline reserve	UNE 26-388	3.0 - 6.0 ml HCl 0.1M
Freezing point	UNE 26-391	-35 °C ± 2 °C

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS

- AS 2108-2004, ASTM D 3306, ASTM D 4985, ASTM D 6210,
- SAE J1034, ÖNORM V 5123, CUNA NC 956-16, JIS K 2234:2006, Cummins CES 14603.
- SANS 1251:2005, SH 0521-1999 and BS 6580:2010
- MB 325.5 - MB 325.6 - MB 326.5 – MB 326.6
- MAN 324 Type Si-OAT
- SCANIA TB1451 – EURO 6