



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

ALTAIR 0W20 508.509

ED-01
Feb-23

DESCRIPTION:

Fully synthetic lubricant for mandatory use in new VAG GROUP engines (Audi, Seat, Skoda). Formulated to prolong the life of emission systems and maintain their efficiency, provide excellent engine cleanliness

CHARACTERISTICS:

- Employs 100% synthetic technology
- Combines synthetic technology to provide increased protection in both high and low temperature applications
- Offers continued protection in all driving styles and temperatures
- Provides superior performance in extreme cold start conditions
- Excellent fuel economy and reduced CO2 emissions
- 0W-20 viscosity grade lubricant with reduced ash content and low high temperature and shear viscosity, HTHS ≥ 2.6 mPa.s.

HOW TO USE IT:

Suitable for petrol and diesel vehicles. Product formulated for its mandatory use in new engines 2.0 TFSI 140 kW and 3.0 TDI CR 160 kW from VW and Audi that require specification 508 00 and 509 00.

TECHNICAL DATA:

Description :	100% sythetic engine oil
----------------------	--------------------------

Aspect:	Clear and bright fluid
----------------	------------------------

Viscosity at 100°C :	ASTM D-445 5.6-9.3 cST.
-----------------------------	--------------------------------

Viscosity index:	ASTM D2270 160 minimum
-------------------------	-------------------------------

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available through the IADA Customer Service Centre.

QUALITY LEVELS:

VW - 508 00/509 00 - VW TL 525 77 - PORSCHE C20

ACEA C5 – API SN – PLUS