



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

TOPTRUCK 5W30 FUEL ECONOMY

ED-03
ENE 2025

DESCRIPTION:

100% synthetic lubricant of the highest performance and quality, formulated for exceptional fuel economy for heavy duty vehicles with exhaust after-treatment and turbocharging. Its advanced additive technology delivers fuel-saving performance over long shift periods, helping to reduce operating costs.

Optimal cold start, lower oil consumption and reduced emissions, it is an ideal product for Euro VI engines.

CHARACTERISTICS:

Formulated to offer high corrosion protection to bearings, helping to increase engine life. High rust protection. Very fast starting lubrication due to its low viscosity. Improved cold start characteristics. Advanced additive technology offers fuel saving performance over long change periods, helping to reduce operating costs. Results show fuel savings of up to 4% on stationary starts and 2.5% on long haul.

APPLICATIONS - HOW TO USE IT:

Ideal for use in mixed fleets of long-haul trucks and buses with multi-brand Euro V and Euro VI engines, but also suitable for older engines, as well as gas engines running on CNG.

Designed to meet the lubrication requirements for high performance, latest generation type 6 diesel engines, where low levels of sulphated ash, phosphorus and sulphur are required.

Recommended for Euro VI and earlier engines.

Especially suitable for after-treatment systems such as particulate filters (DPF), continuous generation traps (CRT) and EcoBlue® selective catalytic reduction by injection (SCR) systems that require low ash oils, optimising engine life and saving on maintenance.

TECHNICAL DATA

Description :	Aceite 100 % sintétic - 100% synthetic oil
Aspect :	Bright and clear fluid
Viscosity at 100°C :	ASTM D-445 9.5 - 12.5 cST.
Viscosity index:	ASTM D2270 150 minimum

** We reserve the right to modify the general characteristics of our products in order to enable our customers to benefit from the latest technical developments. For further product information, please refer to the Safety Data Sheet (SDS), available from the IADA Customer Service Centre.



TECHNICAL DATA SHEET

Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

TOPTRUCK 5W30 FUEL ECONOMY

ED-02
FEB 2021

QUALITY LEVELS

API CK-4 - API CJ-4/SN

ACEA E6 (16) / ACEA E7(22) / ACEA E8(22) / ACEA E9(16) /ACEA E11 (22)

MB-Approval 228.51 DTFR15C110

MAN M3775

MTU Type 3.1

Volvo VDS-4 - VDS-4.5

JASO DH-2

CAT ECF-3

DEUTZ DQC IV-10LA DQC IV-18LA

Detroit Diesel DDC 93K218 DDC 93K222

Cummins CES 20076 CUMMINS CES 20077 CUMMINS CES 20078 CUMMINS CES 20081 20086

MACK EO-O Premium Plus-07

MACK EOS-4.5

MACK EO-N Premium Plus

MACK EO-M Plus

Renault Truck RLD-3 Mack EOS 4.5

Voith Retarder Class B

Scania Low Ash

Scania LDF-4