



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobí del Penedes (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

ATF MULTI-VEHICLE

DESCRIPTION:

ED-04
JUL-13

Fluid for 100% synthetic multi-vehicle transmissions for European, American and Asian vehicles.

Last generation technology that meets the demands of today's transmissions and surpasses the performance of the old ones.

It complies with the latest specification of Ford (Mercon V), Chrysler +4, General Motors Dexron IIIH and the requirements of several Mercedes standards. It allows a solution in a product to a wide range of vehicle brands.

For Tiptronic gearboxes (GRUPO VAG).

It covers the needs of most import vehicles complying with Honda / KIA SP-III, Nissan Matic D, J, K, Toyota T-III, T-IV standards.

CHARACTERISTICS:

- Formulated with antifriction additives to overcome the demanding performance of Asian vehicles
- It protects the gears of the transmission allowing a smooth operation and without blows of the transmission
- Friction stability and anti-wear performance
- High viscosity index and excellent viscosity stability in service
- Extended oil changes; greater durability
- High shear stability
- Protection against wear and corrosion of the system, extending the life of the mechanism
- Prevents oil aging (oxidation). Control of sludge and varnish formation
- Great thermal and film stability; even at high operating temperatures
- Excellent behavior at low temperatures, very important when starting the vehicle
- Fully compatible with rubber gaskets. High resistance to form foams.
- Reduces fluid diversity.
- Exceeds benefits under severe conditions.

HOW TO USE IT:

Automatic transmissions, power steering, power steering of light vehicles, trucks, buses, commercial vehicles. Multifunctional application, allowing a reduction of products in the workshop. Do not use in variable gearboxes (CVT) or double clutch gearboxes (DSG).

TECHNICAL DATA:

Description :	Lubricant for automatic transmissions	
Color:	Visual	Red
Viscosity at - 40°C :	ASTM D-445	33-38 cSt maximum
Viscosity at 100°C :	ASTM D-445	7.0/8.0 cSt
pH:	ASTM D-2270	170 minimum

We reserve the right to modify the general characteristics of our products in order to facilitate that our clients benefit from the latest technical advances. For more information about the product, it is recommended to consult the Safety Data Sheet (SDS), available through the Customer Service Center in IADA.

QUALITY LEVELS:

Allison C4, TES-295
BMW LT71141, LA2634, ETL-7045, 8072B
Caterpillar TO-2
Chrysler +3, +4
Ford MERCON®V
GM Dexron II, Dexron III(H)
HMC/KIA SP-III
Honda Z1
Jaguar Idemitsu K17
Jaso M315-2004

Land Rover Texaco N402
MAN 339V1, 339Z2
Mazda ATF M-III, M5
MB 236.03, 05, 06, 07, 09, 10, 11, ATF 3403
Nissan Matic D, J, K
Subaru ATF, plus ATF-HP
Toyota T-III, T-IV
Voith H55.6335.xx
Volvo Std 1273,40