



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

MULTITECH 5W30 C3/C2

ED-01
MARZO 2017

DESCRIPTION:

100% Synthetic oil, designed especially for vehicles with Gasoline or Diesel engines Euro 4 and Euro 5 that require an ACEA C3 / C2 lubricant, with high viscosity HTHS and "Mid SAPS"

CHARACTERISTICS:

- Employs 100% synthetic technology
- Adheres to metal surfaces making the parts of the motor more resistant to wear
- Combines synthetic technology to provide greater protection in applications with high and low temperatures
- Provides continued protection in any driving style and temperatures
- Provide superior performance under extreme cold start conditions.

HOW TO USE IT:

Oil compatible with catalytics converters and diesel particulate filters (DPF). Before use, always consult with your vehicle instructions book..

TECHNICAL DATA:

Description:	Oil 100 % synthetic
Aspect :	Clear and bright fluid
Viscosity at 100°C :	ASTM D-445 9.3 -12.5 cST.
Viscosity index:	ASTM D2270 150 minimum

QUALITY LEVELS:

ACEA C3/C2

API SN

MB 229.31