



Ctra.Vilafranca-Guardiola Km 6.5
80735 – Vilobi del Penedes (Barcelona)
+34938978437 www.iada.es

TECHNICAL DATA SHEET

MONOGRADE SAE 30

ED-04
MAR-14

DESCRIPTION:

Monograde mineral oil formulated for diesel engines, recommended for moderately low ambient temperatures (such as typical winter temperatures in central and southern Europe). For aspirated and slightly supercharged diesel engines with frequent drainage periods

CHARACTERISTICS:

High detergent - dispersant power, which provides adequate cleaning in the internal parts of the engine.
Excellent protection against wear and corrosion. Extends the life of the engine.
Adequate alkaline reserve, neutralizing acids formed during engine work.
High resistance to foam formation.
Great stability to oxidation.

HOW TO USE IT:

In atmospheric or turbo diesel engines, in any type of vehicle, trucks, coaches.
With normal drainage periods.

TECHNICAL DATA:

Description :	MINERAL OIL FOR DIESEL ENGINES	
Aspect :	Visual	Clear and bright fluid
Visosity Index:	ASTM D2270	95 minimum
Viscosity at 40° C:	ASTM D445	95 cSt
Viscosity at 100° C:	ASTM D445	9.3 - 12.5 cSt
TBN	ASTM D2896	6.9 mg KOH/g minimum

We reserve the right to modify the general characteristics of our products in order to facilitate that our clients benefit from the latest technical advances. For more information about the product, it is recommended to consult the Safety Data Sheet (SDS), available through the Customer Service Center in IADA.

QUALITY LEVELS:

API SG/CF

ACEA E2

MB 228.0

Allison C-4

