

PRODUCT DESCRIPTION

High quality lubricant with synthetic components for automatic transmissions and assisted directions; whenever it is recommended a fluid meeting specification GM Dexron IIIG.

CHARACTERISTICS

- High viscosity index and excellent viscosity stability when working.
- Excellent power transmission.
- Great wear protection, with longer transmission life.
- Great ageing resistance to sludge formation.
- Provides a quiet operation and smooth shifting.
- Superb protection against rust and corrosion and good flow – viscosity at low starting temperatures.
- Resistance to foaming.
- Compatibility with synthetic rubber seal materials.

TECHNICAL INFORMATION

Appearance / Colour :		Bright fluid. Red colour.
Viscosity Index	ASTM D-2270	170
Viscosity @ 100°C	ASTM D 445	7.6 cSt min.
Viscosity @ 40°C:	ASTM D 445	38 cSt

*** Nos reservamos el derecho de modificar las características generales de nuestros productos con el fin de facilitar que nuestros clientes se beneficien de los últimos avances técnicos. Para mayor información sobre el producto se recomienda consultar la Ficha de Datos de Seguridad (FDS), disponible a través del Centro del Servicio al cliente en IADA.*

QUALITY LEVELS

Automatic transmissions, servomechanisms, assisted directions of vehicles, trucks, public and agricultural machinery, and also all kind of machines, all brands (as long as they require differently), hydraulic systems, etc. In general, whenever it is required a quality DEXRON III-G

Important: Do not use Hydraulic LHM where synthetic brake fluids meeting DOT 3, DOT 4, DOT 5.1, etc. are required.

- GM DEXRON IIIG
- FORD MERCON
- ALLISON C-4
- MB 236.9
- ZF TE-ML 9B/11B/14A
- Caterpillar TO-2
- Man 339F
- Voith 55.6335