

PRODUCT DESCRIPTION

Hydraulic fluid 100% synthetic base for power steering systems, formulated with a wide range of additives which grant the proper qualities for the demanding working conditions to it is appointed to.

Special for vehicles: Volkswagen, Audi, Seat.

CHARACTERISTICS

Very high viscosity index. Excellent power transmission at any ambient temperature.

High anticorrosive and antirust power. High durability.

Great anti wear power. Grants a soft functioning with no vibrations.

Does not form foam. Great stability in front of rubber joints. Easily to identify due to its colour.

TECHNICAL INFORMATION

Appearance / Colour:		Bright fluid / Green
Viscosity @40°C :	ASTM D-445	16 – 20 cSt
Viscosity @100°C :	ASTM D-445	> 6 cSt
Viscosity index:	ASTM D2270	310
Flash Point:	UNE 51-023	162°C

** Nos reservamos el derecho de modificar las características generales de nuestros productos con el fin de facilitar que nuestros clientes se beneficien de los últimos avances técnicos. Para mayor información sobre el producto se recomienda consultar la Ficha de Datos de Seguridad (FDS), disponible a través del Centro del Servicio al cliente en IADA.

QUALITY LEVELS

Its application is only for power steering which need a hydraulic fluid with this characteristics. Specially for vehicles: Volkswagen, Audi, Seat.

WV TL 52146
MB 345.0
FORD 12C 204A